

S-RACK

Enclosures Wallmounting 19", IP55

SCHRACK
TECHNIK



SCAN AND BUY

in our mobile Online Shop


INCL. AVAILABILITY INFORMATION



Ex stock

Schrack Technik Online Shop

Schrack Technik offers products and solutions for energy technology, industrial power applications, building automation and technology, emergency lighting, network technology, lighting, and alternative energy. Easy and secure online shopping.




ORDER ONLINE & REAP THE BENEFITS



Fast Delivery



**Personal consulting
& top pricing**



**Order online
& save time**



Personal contact

Your advantages

- ✓ TOP Quality - TOP Availability
- ✓ Really attractive price
- ✓ Fast delivery

S-RACK

Data Enclosures Wallmounting 19", IP55

▀ Data Enclosures Wallmounting 19", IP55

Data Enclosures Wallmounting 19", IP55 Indoor, Width = 600mm, Depth = 450mm	Page 4
Data Enclosures Wallmounting 19", IP55 Outdoor, Width = 600mm, Depth = 450mm.....	Page 7
Data Enclosures Wallmounting 19", IP55 Outdoor, Width = 600mm, Depth = 600mm.....	Page 10
Fan Units for Wallmounting Enclosures, IP55	Page 13
Plinth.....	Page 14
Pole Assembly Kit	Page 15

■ Data Enclosures Wallmounting 19", IP55 Indoor, Width = 600mm, Depth = 450mm



DTWI076040



DTWI096040



DTWI126040



DTWI166040



DTWI076042



DTWI096042



DTWI126042



DTWI166042

■ Schrack-Info

Network wallmount 19" IP55 Indoor Cabinets are designed for industrial applications.

Based on EN60529 provides IP55 protection class against dust and water ingress.

The enclosure provides IP55 protection against dust and water.

After installation of fans or filters, IP54 is still met.

Application areas are semi-open areas like factories, warehouses, lean-to roof conditions, without no direct rain and environmental effects.

Totally gasketed doors, IP55 performing swing handle locking with 3 point locking system and isolated cable entries provide best performance for water and dust ingress.

1,5 mm thick material monoblock welded construction, with epoxy polyester type powder coating which is RAL7035 Light Grey color, provides corrosion resistance.

Passive ventilation via filtered inlets.

Option to install fans for active ventilation.

■ Technical Data


- Colour: RAL7035 Light Grey
- Front door opening angle is up to 140 degrees. Front door has an infused sealing gasket structure which provides excellent IP protection even under cold/hot weather conditions. The front door is grounded to the main body with yellow/green 4,0 mm diameter copper wire.
- Heights: 7, 9, 12 and 16U
- Width: 600mm
- Depth: 450mm
- Maximum Load: 100kg
- Door: Glass and Metal door including keyed swing lock handle with 3 point locking system provides security and anti-vandal structure, also maintaining the IP55 protection
- Included are 4 pcs 3.0mm thick wall mounts with matching washer and screws, as well as a cable entry flange with three glands: 2 x PG21, 1 x PG48, 2 x PVC blind caps with 28mm diameter (installed in the floor) and a blind flange (accessory pack).
- Filters are included
- Cabinets are delivered with: 1 set = 2 pcs 19" front rails



Mobil Code

■ Data Enclosures Wallmounting 19", IP55 Indoor, Width = 600mm, Depth = 450mm

■ DTWlxxx4x Technical Drawing



A Top View	D Front View	G Top Inside View
B Bottom View	E Side View	I Front Door Opening Angle
C Inside View	F Rear View	J 3 Point Locking System

- 1) 260 up to 385mm.
- 2) 60 up to 185mm.


Type	h [mm]	H [mm]	Weight Net [kg]	Gross Weight [kg]
DTWI076040	311	440	27	28
DTWI096040	400	529	30.5	31.5
DTWI126040	533	663	33.5	34.5
DTWI166040	711	841	37.2	38.2
DTWI076042	311	440	25	26
DTWI096042	400	529	28	29
DTWI126042	533	663	31	32
DTWI166042	711	841	37	38

X	298mm (7U)	387mm (9U)	520mm (12U)	698mm (16U)
----------	------------	------------	-------------	-------------

Data Enclosures Wallmounting 19", IP55

▀ Data Enclosures Wallmounting 19", IP55 Indoor, Width = 600mm, Depth = 450mm

▀ DTWlxxxx4x Technical Drawing



A	19" Rail
B	Front Door
C	Fan (optional)
D	Filter
E	Assembled on the cabinets
F	Spare grand plate supplied loose inside cabinet

DESCRIPTION	AVAILABLE	ORDER NO.
Network Enclosure Wallmounting with Metaldoor, IP55, Indoor, RAL7035, W=600, H=440, D=450, 19", 7U		DTWI076042
Network Enclosure Wallmounting with Metaldoor, IP55, Indoor, RAL7035, W=600, H=529, D=450, 19", 9U		DTWI096042
Network Enclosure Wallmounting with Metaldoor, IP55, Indoor, RAL7035, W=600, H=663, D=450, 19", 12U		DTWI126042
Network Enclosure Wallmounting with Metaldoor, IP55, Indoor, RAL7035, W=600, H=841, D=450, 19", 16U		DTWI166042
Network Enclosure Wallmounting with Glasdoor, IP55, Indoor, RAL7035, W=600, H=440, D=450, 19", 7U		DTWI076040
Network Enclosure Wallmounting with Glasdoor, IP55, Indoor, RAL7035, W=600, H=529, D=450, 19", 9U		DTWI096040
Network Enclosure Wallmounting with Glasdoor, IP55, Indoor, RAL7035, W=600, H=663, D=450, 19", 12U		DTWI126040
Network Enclosure Wallmounting with Glasdoor, IP55, Indoor, RAL7035, W=600, H=841, D=450, 19", 16U		DTWI166040

■ Data Enclosures Wallmounting 19", IP55 Outdoor, Width = 600mm, Depth = 450mm



DTWI076047



DTWI096047



DTWI126047



DTWI166047

■ Schrack-Info

Network wallmount 19" IP55 Outdoor Cabinets are designed for industrial applications.

Based on EN60529 provides IP55 protection class against dust and water ingress.

The enclosure provides IP55 protection against dust and water.

After installation of fans or filters, IP54 is still met.

Application: Outdoor areas under environment influences.

Protection of the installed equipment against ingress of solid foreign objects (falling dirt and windblown dust) and against the ingress of water (rain, sleet, snow, splashing water).

Gasketed doors IP55.

3 point locking system with swing handle. Isolated cable entries.

1,5 mm thick material monoblock welded construction, with epoxy polyester type powder coating which is RAL7035 Light Grey color, provides corrosion resistance.

Passive ventilation via filtered inlets.

Option to install fans for active ventilation.

Outdoor cabinets have a fan cover in the top view and side filter covers to comply with protection class IP55.

■ Technical Data


- Colour: RAL7035 Light Grey
- Front door opening angle is up to 140 degrees. Front door has an infused sealing gasket structure which provides excellent IP protection even under cold/hot weather conditions. The front door is grounded to the main body with yellow/green 4,0 mm diameter copper wire.
- Heights: 7, 9, 12 and 16U
- Width: 600mm
- Depth: 450mm
- Maximum Load: 100kg
- Door: Metal door including keyed swing lock handle with 3 point locking system provides security and anti-vandal structure, also maintaining the IP55 protection.
- Included are 4 pcs 3.0mm thick wall mounts with matching washer and screws, as well as a cable entry flange with three glands: 2 x PG21, 1 x PG48, 2 x PVC blind caps with 28mm diameter (installed in the floor) and a blind flange (accessory pack).
- Filters are included.
- Cabinets are delivered with: 1 set = 2 pcs 19" front rails



Mobil Code

■ Data Enclosures Wallmounting 19", IP55 Outdoor, Width = 600mm, Depth = 450mm

■ DTWIxxxx47 Technical Drawing



A Top View	D Front View	G Top Inside View
B Bottom View	E Side View	I Front Door Opening Angle
C Inside View	F Rear View	J 3 Point Locking System


1) 260 up to 385mm
2) 60 up to 185mm

Type	h [mm]	H [mm]	Weight Net [kg]	Gross Weight [kg]
DTWI076047	311	490	31	32
DTWI096047	400	579	33	34
DTWI126047	533	713	37	38
DTWI166047	711	891	41	43

X	298mm (7U)	387mm (9U)	520mm (12U)	698mm (16U)
----------	------------	------------	-------------	-------------

■ Data Enclosures Wallmounting 19", IP55 Outdoor, Width = 600mm, Depth = 450mm

■ DTWIxxxx47 Technical Drawing



A	19" Rail
B	Front Door
C	Fan (optional)
D	Filter
E	Assembled on the cabinets
F	Spare grand plate supplied loose inside cabinet
G	Inclined roof

DESCRIPTION	AVAILABLE	ORDER NO.
Network Enclosure Wallmounting with Metaldoor, IP55, Outdoor, RAL7035, W=600, H=490, D=450, 19", 7U		DTWI076047
Network Enclosure Wallmounting with Metaldoor, IP55, Outdoor, RAL7035, W=600, H=579, D=450, 19", 9U		DTWI096047
Network Enclosure Wallmounting with Metaldoor, IP55, Outdoor, RAL7035, W=600, H=713, D=450, 19", 12U		DTWI126047
Network Enclosure Wallmounting with Metaldoor, IP55, Outdoor, RAL7035, W=600, H=891, D=450, 19", 16U		DTWI166047



On stock, usually ready for delivery on the day of order

■ Data Enclosures Wallmounting 19", IP55 Outdoor, Width = 600mm, Depth = 600mm



DTWI206067

■ Schrack-Info

Network wallmount 19" IP55 Outdoor Cabinets are designed for industrial applications.

Based on EN60529 provides IP55 protection class against dust and water ingress.

The enclosure provides IP55 protection against dust and water.

After installation of fans or filters, IP54 is still met.

Application: Outdoor areas under environment influences.

Protection of the installed equipment against ingress of solid foreign objects (falling dirt and windblown dust) and against the ingress of water (rain, sleet, snow, splashing water).

Gasketed doors IP55.

3 point locking system with swing handle. Isolated cable entries.

1,5 mm thick material monoblock welded construction, with epoxy polyester type powder coating which is RAL7035 Light Grey color, provides corrosion resistance.

Passive ventilation via filtered inlets.

Option to install fans for active ventilation.

Outdoor cabinets have a fan cover in the top view and side filter covers to comply with protection class IP55.

■ Technical Data


- Colour: RAL7035 Light Grey
- Front door opening angle is up to 140 degrees. Front door has an infused sealing gasket structure which provides excellent IP protection even under cold/hot weather conditions. The front door is grounded to the main body with yellow/green 4,0 mm diameter copper wire.
- Height: 20U
- Width: 600mm
- Depth: 600mm
- Maximum Load: 100kg
- Door: Metal door including keyed swing lock handle with 3 point locking system provides security and anti-vandal structure, also maintaining the IP55 protection.
- Included are 4 pcs 3.0mm thick wall mounts with matching washer and screws, as well as a cable entry flange with three glands: 2 x PG21, 1 x PG48, 2 x PVC blind caps with 28mm diameter (installed in the floor) and a blind flange (accessory pack).
- Filters are included
- Cabinets are delivered with: 1 set = 2 pcs 19" front rails



Mobil Code

■ Data Enclosures Wallmounting 19", IP55 Outdoor, Width = 600mm, Depth = 600mm

■ DTWI206067 Technical Drawing



A Top View	D Front View	G Top Inside View
B Bottom View	E Side View	I Front Door Opening Angle
C Inside View	F Rear View	J 3 Point Locking System


1) 260 up to 535mm.
2) 60 up to 335mm.

Type	h [mm]	H [mm]	Weight Net [kg]	Gross Weight [kg]
DTWI206067	889	1068	58	59.5

X 876mm (20U)

■ Data Enclosures Wallmounting 19", IP55 Outdoor, Width = 600mm, Depth = 600mm

■ DTWI206067 Technical Drawing




A	19" Rail
B	Front Door
C	Fan (optional)
D	Filter
E	Assembled on the cabinets
F	Spare grand plate supplied loose inside cabinet
G	Inclined roof

DESCRIPTION

Network Enclosure Wallmounting with Metaldoor, IP55, Outdoor, RAL7035, W=600, H=1068, D=600, 19", 20U

AVAILABLE ORDER NO.



DTWI206067

Fan Units for Wallmounting Enclosures, IP55



DTLTR5522-



DTLTR5521-

Technical Data

Fan min / max:

- 11.8 / 13.8W
- 220 / 240V AC
- 50 / 60Hz



Mobil Code

Schrack-Info

Ready pre-installed, → plug and play.

Included thermostat adjustable from 0 - 60°C.

Each fan has an airflow capacity of 2.63 - 3.03cbm/min.

Suitable for both INDOOR and OUTDOOR variants of DTWI IP55 cabinets.

By installing the fan, the IP protection is reduced to IP54.

- 0.12 / 0.14A
- 2550/2750 rpm
- 43 - 47db-A noise level.
- Fan life: 50,000 hours at 40 ° C.

DESCRIPTION	AVAILABLE	ORDER NO.
Roof Fan-unit IP54, 1 fan, for DTWI wallmounting enclosures IP55, switch (on/off), RAL7035, light grey, Installation from outside of enclosure		DTLTR5521
Roof Fan-unit IP54, 2 fans, for DTWI wallmounting enclosures IP55, switch (on/off), RAL7035, light grey, Installation from outside of enclosure		DTLTR5522



On stock, usually ready for delivery on the day of order

Plinth



DTOT110606



DTOT110604



Mobil Code

Schrack-Info

100mm height.

For installation under the cabinet floor.

To create space for cable reserves, as well as to raise the cabinet to a height from the concrete basement.

Fastening at 4 corners with M12 screws and nuts. (Not included in the delivery).

DESCRIPTION	AVAILABLE	ORDER NO.
Base set H=100 for concrete Basement and DTWI wall mounting enclosures IP55, W=600, D=450, RAL7035		DTOT110604
Base set H=100 for concrete Basement and DTWI wallmount enclosures IP55, W=600, D=600, RAL7035		DTOT110606

Pole Assembly Kit



DTWIPAK---



Mobil Code

Schrack-Info

For pole diameter: 10 - 15cm.

Galvanized.

The set consists of 2 mast mounting brackets + 2 mounting brackets for the cabinet and a set of screws.

DESCRIPTION	AVAILABLE	ORDER NO.
Mast Assembly Kit for Mast diameter 10-15cm, zinc plated, 2x Mast brackets + 2x mounting brackets for cabinet + screws		DTWIPAK



On stock, usually ready for delivery on the day of order

THE COMPANY

HEADQUARTERS

SCHRACK TECHNIK GMBH

Seybelgasse 13, 1230 Vienna
PHONE +43(0)1/866 85-5900
FAX +43(0)1/866 85-98800
E-MAIL info@schrack.at

SCHRACK SUBSIDIARIES

BELGIUM

SCHRACK TECHNIK B.V.B.A
Twaalfapostelenstraat 14
BE-9051 St-Denijs-Westrem
PHONE +32 9/384 79 92
FAX +32 9/384 87 69
E-MAIL info@schrack.be

BOSNIA-HERZEGOVINA

SCHRACK TECHNIK BH D.O.O.
Put za aluminijski kombinat bb
BH-88000 Mostar
PHONE +387/36 352 895
FAX +387/36 352 893
E-MAIL schrack@schrack.ba

BULGARIA

SCHRACK TECHNIK EOOD
Prof. Tsvetan Lazarov 162
Druzhba - 2
BG-1582 Sofia
PHONE +359 2/890 79 13
FAX +359 2/890 79 30
E-MAIL sofia@schrack.bg

CROATIA

SCHRACK TECHNIK D.O.O.
Zavrtnica 17
HR-10000 Zagreb
PHONE +385 1/605 55 00
FAX +385 1/605 55 66
E-MAIL schrack@schrack.hr

CZECH REPUBLIC

SCHRACK TECHNIK SPOL. SR.O.
Dolnomecholupska 2
CZ-10200 Praha 10 – Hostivar
PHONE +420 (0)2/810 08 264
FAX +420 (0)2/810 08 462
E-MAIL praha@schrack.cz

HUNGARY

SCHRACK TECHNIK KFT.
Vidor u. 5
H-1172 Budapest
PHONE +36 1/253 14 01
FAX +36 1/253 14 91
E-MAIL schrack@schrack.hu

GERMANY

SCHRACK TECHNIK GMBH
Thomas-Wimmer-Ring 17
D-80539 Munich
PHONE +49 89/999 533 900
FAX +49 89/999 533 902
E-MAIL info@schrack-technik.de

POLAND

SCHRACK TECHNIK POLSKA
SP.ZO.O.
ul. Staniewicka 5
PL-03-310 Warszawa
PHONE +48 22/205 31 00
FAX +48 22/205 31 01
E-MAIL kontakt@schrack.pl

ROMANIA

SCHRACK TECHNIK SRL
B-dul lului Maniu nr 453-457, sect. 6
RO-061101 Bucharest
PHONE +40 21/317 02 35 42
FAX +40 21/317 02 62
E-MAIL bucuresti@schrack.ro

SERBIA

SCHRACK TECHNIK D.O.O.
Bulevar Peka Dapčevića 42
RS-11000 Beograd
PHONE +38 1/11 309 2600
FAX +38 1/11 309 2620
E-MAIL office@schrack.rs

SLOVAKIA

SCHRACK TECHNIK S.R.O.
Ivanská cesta 10/C
SK-82104 Bratislava
PHONE +421 (02)/491 081 01
FAX +421 (02)/491 081 99
E-MAIL info@schrack.sk

SLOVENIA

SCHRACK TECHNIK D.O.O.
Pameče 175
SLO-2380 Slovenj Gradec
PHONE +38 6/2 883 92 00
FAX +38 6/2 884 34 71
E-MAIL schrack.sg@schrack.si



WWW.SCHRACK.COM

